SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 1/41

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name: Propane, pure substance

Trade name: REN propane, R290, Propane Scientific 3.5

Additional identification

Chemical name:	Propane
Chemical formula:	C3H8
INDEX No.	601-003-00-5
CAS-No.	74-98-6
EC No.	200-827-9
REACH Registration No.	01-2119486944-21

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses: Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use. Under controlled conditions.
Aerosol propellant. Refrigerant. Transfilling gas or liquid, Use as a fuel Using gas alone or in mixtures for the calibration of analysis equipment. Formulation of mixtures with gas in pressure receptacles. Consumer use.

Uses advised against Contact supplier for more information on uses. Uses other than those listed above are not supported.

1.3 Details of the supplier of the safety data sheet

Supplier

Linde Gas AB
Rättarvägen 3
169 68 Solna

Telephone: +46 8 7069500

E-mail: sds.ren@linde.com

1.4 Emergency telephone number: Poison center: 020-99 60 00 (24 h). Emergency number: 112

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 2/41

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended.

Physical Hazards

Flammable gas	Category 1A	H220: Extremely flammable gas.
Gases under pressure	Liquefied gas	H280: Contains gas under pressure; may explode if heated.

2.2 Label Elements

Signal Word: Danger

Hazard Statement(s):
H220: Extremely flammable gas.
H280: Contains gas under pressure; may explode if heated.

Precautionary Statements

General None.

Prevention: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response: P377: Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381: In case of leakage, eliminate all ignition sources.

Storage: P403: Store in a well-ventilated place.

Disposal None.

2.3 Other hazards

Contact with evaporating liquid may cause frostbite or freezing of skin.

Endocrine disrupting properties-Toxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Endocrine disrupting properties-Ecotoxicity

The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

SECTION 3: Composition/information on ingredients

3.1 Substances

Chemical name Propane
INDEX No.: 601-003-00-5
CAS-No.: 74-98-6
EC No.: 200-827-9
REACH Registration No.: 01-2119486944-21
Purity: 100%
The purity of the substance in this section is used for classification only, and does not represent the actual purity of the substance as supplied, for which other documentation should be consulted.
Trade name: REN propane, R290, Propane Scientific 3.5

Chemical name	Chemical formula	Concentration	CAS-No.	EC No.	REACH Registration No.	M-Factor:	Notes
Propane	C3H8	100%	74-98-6	200-827-9	01-2119486944-21	-	

The concentrations of the components in the SDS header, product name on page one and in section 3.2 are in mol due to regulatory requirements. All concentrations are nominal.
This substance has workplace exposure limit(s).
This substance is listed as SVHC.PBT: persistent, bioaccumulative and toxic substance.
vPvB: very persistent and very bioaccumulative substance.

SECTION 4: First aid measures

General: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

4.1 Description of first aid measures

Inhalation: In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

Eye contact: Rinse the eye with water immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Flush thoroughly with water for at least 15 minutes. Get immediate medical assistance. If medical assistance is not immediately available, flush an additional 15 minutes.

Skin Contact: Contact with evaporating liquid may cause frostbite or freezing of skin. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Get medical attention.

Ingestion: Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling. Loss of co-ordination. In low concentrations may cause narcotic effects. Dizziness. Headache. Unconsciousness. Nausea, vomiting.

4.3 Indication of any immediate medical attention and special treatment needed

Hazards: Respiratory arrest. Contact with liquefied gas can cause damage (frostbite) due to rapid evaporative cooling.

Treatment: Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

SECTION 5: Firefighting measures

General Fire Hazards: Heat may cause the containers to explode.

5.1 Extinguishing media

Suitable extinguishing media: Water Spray or Fog. Dry powder. Foam.

Unsuitable extinguishing media: Carbon Dioxide.

5.2 Special hazards arising from the substance or mixture: May explode in a fire.

Hazardous Combustion Products: Incomplete combustion may form carbon monoxide

5.3 Advice for firefighters

Special fire-fighting procedures:	In case of fire: Stop leak if safe to do so. Do not extinguish flames at leak because possibility of uncontrolled explosive reignition exists. Continue water spray from protected position until container stays cool. Use extinguishants to contain the fire. Isolate the source of the fire or let it burn out.
Special protective equipment for fire-fighters:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Guideline: EN 469 Protective clothing for firefighters. Performance requirements for protective clothing for firefighting. EN 15090 Footwear for firefighters. EN 659 Protective gloves for firefighters. EN 443 Helmets for fire fighting in buildings and other structures. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:	Evacuate area. Provide adequate ventilation. Consider the risk of potentially explosive atmospheres . In case of leakage, eliminate all ignition sources. Monitor the concentration of the released product. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
6.2 Environmental Precautions:	Prevent further leakage or spillage if safe to do so.
6.3 Methods and material for containment and cleaning up:	Provide adequate ventilation. Eliminate sources of ignition.
6.4 Reference to other sections:	Refer to sections 8 and 13.

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 7/41

SECTION 7: Handling and storage:

7.1 Precautions for safe handling:

Only experienced and properly instructed persons should handle gases under pressure. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Purge air from system before introducing gas. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Assess the risk of a potentially explosive atmosphere and the need for suitable equipment i.e. explosion-proof. Take precautionary measures against static discharges. Keep away from ignition sources (including static discharges). Provide electrical earthing of equipment and electrical equipment usable in explosive atmospheres. Use non-sparking tools. Refer to supplier's handling instructions. The substance must be handled in accordance with good industrial hygiene and safety procedures. Ensure the complete system has been (or is regularly) checked for leaks before use. Protect containers from physical damage; do not drag, roll, slide or drop. Do not remove or deface labels provided by the supplier for the identification of the container contents. When moving containers, even for short distances, use appropriate equipment eg. trolley, hand truck, fork truck etc. Secure cylinders in an upright position at all times, close all valves when not in use. Provide adequate ventilation. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Avoid suckback of water, acid and alkalis. Keep container below 50°C in a well ventilated place. Observe all regulations and local requirements regarding storage of containers. When using do not eat, drink or smoke. Store in accordance with local/regional/national/international regulations. Never use direct flame or electrical heating devices to raise the pressure of a container. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. Damaged valves should be reported immediately to the supplier Close container valve after each use and when empty, even if still connected to equipment. Never attempt to repair or modify container valves or safety relief devices. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Keep container valve outlets clean and free from contaminates particularly oil and water. If user experiences any difficulty operating container valve discontinue use and contact supplier. Never attempt to transfer gases from one container to another. Container valve guards or caps should be in place.

7.2 Conditions for safe storage, including any incompatibilities: All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere. Segregate from oxidant gases and other oxidants being stored. Containers should not be stored in conditions likely to encourage corrosion. Stored containers should be periodically checked for general conditions and leakage. Container valve guards or caps should be in place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible material.

7.3 Specific end use(s): None.

SECTION 8: Exposure controls/personal protection

8.1 Control Parameters

Occupational Exposure Limits

None of the components have assigned exposure limits.

Biological Limit Values

No biological exposure limits noted for the ingredient(s).

8.2 Exposure controls

Appropriate engineering controls: Consider a work permit system e.g. for maintenance activities. Ensure adequate air ventilation. Provide adequate general and local exhaust ventilation. Keep concentrations well below lower explosion limits. Gas detectors should be used when quantities of flammable gases or vapours may be released. Provide adequate ventilation, including appropriate local extraction, to ensure that the defined occupational exposure limit is not exceeded. Systems under pressure should be regularly checked for leakages. Product to be handled in a closed system. Only use permanent leak tight installations (e.g. welded pipes). Take precautionary measures against static discharges.

Individual protection measures, such as personal protective equipment

General information:

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered. Keep self contained breathing apparatus readily available for emergency use. Personal protective equipment for the body should be selected based on the task being performed and the risks involved. Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment. Do not eat, drink or smoke when using the product.

Eye/face protection:

Safety eyewear, goggles or face-shield to EN166 should be used to avoid exposure to liquid splashes. Wear eye protection to EN 166 when using gases.
Guideline: EN 166 Personal Eye Protection.

Skin protection

Hand Protection:

Guideline: EN 388 Protective gloves against mechanical risks.
Additional Information: Wear working gloves while handling containers
Guideline: EN 511 Protective gloves against cold.
Additional Information: Protective gloves should be used if there is a risk of direct contact or splash.

Body protection:

Wear fire resistant or flame retardant clothing.
Guideline: ISO/TR 2801:2007 Clothing for protection against heat and flame -- General recommendations for selection, care and use of protective clothing.

Other:

Wear safety shoes while handling containers
Guideline: ISO 20345 Personal protective equipment - Safety footwear.

Respiratory Protection:	When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres When allowed by a risk assessment Respiratory Protective Equipment (RPE) may be used The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Self-contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres Guideline: EN 137 Respiratory protective devices - Self-contained open-circuit compressed air breathing apparatus with full face mask - Requirements, testing, marking.
Thermal hazards:	No precautionary measures are necessary.
Hygiene measures:	Specific risk management measures are not required beyond good industrial hygiene and safety procedures. Do not eat, drink or smoke when using the product.
Environmental exposure controls:	For waste disposal, see section 13 of the SDS.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state:	Gas
Form:	Liquefied gas
Color:	Colorless
Odor:	Odorless
Odor Threshold:	Odor threshold is subjective and is inadequate to warn of over exposure.
Melting Point:	-305,7 °F/-187,6 °C Experimental result, Key study
Boiling Point:	-43,8 °F/-42,1 °C (1.013 hPa) Experimental result, Key study
Flammability:	This product is not flammable.

Upper/lower limit on flammability or explosive limits

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 11/41

Explosive limit - upper:	10,9 %(V) International standards
Explosive limit - lower:	1,7 %(V)
Flash Point:	-155 °F/-104 °C
Autoignition Temperature:	450 °C Experimental result, Key study
Decomposition Temperature:	1202 °F/650 °C Decomp to ethylene and ethane.
pH:	Not applicable
Viscosity	
Dynamic viscosity:	0,08 mPa.s (64,2 °F/17,9 °C)
Kinematic viscosity:	No data available.
Solubility(ies)	
Solubility in Water:	75 mg/l
Solubility (other):	No data available.
Partition coefficient (n-octanol/water):	2,36
Dispersion Stability:	No data available.
Vapor pressure:	953,25 kPa (77 °F/25 °C)
Relative density:	0,5853 (-49 °F/-45 °C)
Density:	0,493 g/cm3 (77 °F/25 °C) Experimental result, Key study 0,5 g/cm3 (68,0 °F/20,0 °C) 0,45 g/cm3 (122,0 °F/50,0 °C)
Relative vapor density:	1,56 AIR=1 32 °F/0 °C
Particle characteristics:	Not applicable

9.2 Other information

Flammability:	Tci: 3,7
Minimum ignition energy:	0,25 mJ
Molecular weight:	44,09 g/mol (C3H8)
VOC Content:	EC Directive 2004/42: 493 g/l ~100 % (calculated)
Critical Temp. (°C):	96,7 °C

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 12/41

SECTION 10: Stability and reactivity

10.1 Reactivity: No reactivity hazard other than the effects described in sub-section below.

10.2 Chemical Stability: Stable under normal conditions.

10.3 Possibility of hazardous reactions: Can form a potentially explosive atmosphere in air. May react violently with oxidants.

10.4 Conditions to avoid: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5 Incompatible Materials: Air and oxidizers. For material compatibility see latest version of ISO-11114.

10.6 Hazardous Decomposition Products: Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

General information: None.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity - Oral
Product Based on available data, the classification criteria are not met.

Acute toxicity - Dermal
Product Based on available data, the classification criteria are not met.

Acute toxicity - Inhalation
Product Based on available data, the classification criteria are not met.

Repeated dose toxicity
Propane LOAEL (Rat(Female, Male), Inhalation): 21.641 mg/m3 Inhalation Experimental result, Key study

Skin Corrosion/Irritation
Product: Based on available data, the classification criteria are not met.

Serious Eye Damage/Eye Irritation
Product: Based on available data, the classification criteria are not met.

Respiratory or Skin Sensitization
Product: Based on available data, the classification criteria are not met.

Germ Cell Mutagenicity
Product: Based on available data, the classification criteria are not met.

Carcinogenicity
Product: Based on available data, the classification criteria are not met.

Reproductive toxicity
Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Single Exposure
Product: Based on available data, the classification criteria are not met.

Specific Target Organ Toxicity - Repeated Exposure
Product: Based on available data, the classification criteria are not met.

Aspiration Hazard
Product: Not applicable to gases and gas mixtures..

11.2 Information on other hazards

Endocrine disrupting properties
Product: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Components:
Propane: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.;

Other information

Product: No data available.

SECTION 12: Ecological information

General information: Not applicable

12.1 Toxicity

Acute toxicity

Product No ecological damage caused by this product.

Acute toxicity - Aquatic Invertebrates

Propane LC 50 (Daphnia sp., 48 h): 69,43 mg/l Remarks: QSAR QSAR, Key study

12.2 Persistence and Degradability

Product Not applicable to gases and gas mixtures..

Biodegradation

Propane 100 % (385,5 h) Detected in water. Experimental result, Key study

12.3 Bioaccumulative potential

Product The subject product is expected to biodegrade and is not expected to persist for long periods in an aquatic environment.

12.4 Mobility in soil

Product Because of its high volatility, the product is unlikely to cause ground or water pollution.

12.5 Results of PBT and vPvB assessment

Product: Not classified as PBT or vPvB.

Global Warming Potential

Global warming potential: 3
Contains greenhouse gas(es). When discharged in large quantities may contribute to the greenhouse effect.

Propane: EU. Non-Fluorinated Substance GWPs (Annex IV), Regulation 517/2014/EU on fluorinated greenhouse gases
- Global warming potential: 3

12.6 Endocrine disrupting properties:

Product: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Components:

Propane: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects:

Other hazards

Product: No data available.

Other effects:

SECTION 13: Disposal considerations

13.1 Waste treatment methods

General information: Do not discharge into any place where its accumulation could be dangerous. Consult supplier for specific recommendations. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor.

Disposal methods: Refer to the EIGA code of practice (Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org) for more guidance on suitable disposal methods. Dispose of container via supplier only. Discharge, treatment, or disposal may be subject to national, state, or local laws.

European Waste Codes

Container: 16 05 04*: Gases in pressure containers (including halons) containing hazardous substances.

SECTION 14: Transport information

ADR

14.1 UN number or ID number:	UN 1978
14.2 UN Proper Shipping Name:	PROPANE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
Hazard No. (ADR):	23
Tunnel restriction code:	(B/D)
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 17/41

RID

14.1 UN number or ID number:	UN 1978
14.2 UN Proper Shipping Name	PROPANE
14.3 Transport Hazard Class(es)	
Class:	2
Label(s):	2.1
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

IMDG

14.1 UN number or ID number:	UN 1978
14.2 UN Proper Shipping Name:	PROPANE
14.3 Transport Hazard Class(es)	
Class:	2.1
Label(s):	2.1
EmS No.:	F-D, S-U
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.
14.5 Environmental hazards:	Not applicable
14.6 Special precautions for user:	–

IATA

14.1 UN number or ID number:	UN 1978
14.2 Proper Shipping Name:	Propane
14.3 Transport Hazard Class(es):	
Class:	2.1
Label(s):	2.1
14.4 Packing Group:	–
Limited quantity	None.
Excepted quantity	None.

14.5 Environmental hazards: Not applicable
14.6 Special precautions for user: –
Other information
Passenger and cargo aircraft: Forbidden.
Cargo aircraft only: Allowed.

14.7 Maritime transport in bulk according to IMO instruments
Not applicable for product as supplied.

Additional identification: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers ensure that they are firmly secured. Ensure that the container valve is closed and not leaking. Container valve guards or caps should be in place. Ensure adequate air ventilation.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

EU Regulations

EU. REACH Annex XIV, Substances Subject to Authorization as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended: None present or none present in regulated quantities.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended: None present or none present in regulated quantities.

Regulation (EC) No. 1907/2006 Annex XVII Substances subject to restriction on marketing and use:

Chemical name	CAS-No.
Propane	74-98-6

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens and mutagens at work.:

Chemical name	CAS-No.	Concentration
Propane	74-98-6	100%

Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breast feeding.:

Chemical name	CAS-No.	Concentration
Propane	74-98-6	100%

EU. Directive 2012/18/EU (SEVESO III) on major accident hazards involving dangerous substances, Annex I:
Not applicable

National Regulations

Council Directive 89/391/EEC on the introduction of measures to encourage improvements in the safety and health of workers at work Directive 2016/425/EEC on personal protective equipment Directive 2014/34/EU on equipment and protective systems intended for use in potentially explosive atmospheres (ATEX) Only products that comply with the food regulations (EC) No. 1333/2008 and (EU) No. 231/2012 and are labelled as such may be used as food additives.
This Safety Data Sheet has been produced to comply with Regulation (EU) 2020/878.

15.2 Chemical safety assessment: Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Revision Information: Relevant changes are indicated using two vertical bold lines and red text, the text is also highlighted in grey.

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 20/41

Abbreviations and acronyms:

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; EIGA - European Industrial Gases Association; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Key literature references and sources for data:

Various sources of data have been used in the compilation of this SDS, they include but are not exclusive to:
Agency for Toxic Substances and Diseases Registry (ATSDR) (http://www.atsdr.cdc.gov/).
European Chemical Agency: Guidance on the Compilation of Safety Data Sheets.
European Chemical Agency: Information on Registered Substances http://apps.echa.europa.eu/registered/registered-sub.aspx#search
European Industrial Gases Association (EIGA) Doc. 169 "Classification and Labelling guide", as amended.
International Programme on Chemical Safety (http://www.inchem.org/)
ISO 10156:2010 Gases and gas mixtures - Determination of fire potential and oxidizing ability for the selection of cylinder valve outlets.
Matheson Gas Data Book, 7th Edition.
National Institute for Standards and Technology (NIST) Standard Reference Database Number 69.
The ESIS (European chemical Substances 5 Information System) platform of the former European Chemicals Bureau (ECB) ESIS (http://ecb.jrc.ec.europa.eu/esis/).
The European Chemical Industry Council (CEFIC) ERICards.
United States of America's National Library of Medicine's toxicology data network TOXNET (http://toxnet.nlm.nih.gov/index.html)
Threshold Limit Values (TLV) from the American Conference of Governmental Industrial Hygienists (ACGIH).
Substance specific information from suppliers.
Details given in this document are believed to be correct at the time of publication.

Wording of the H-statements in section 2 and 3

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.

Training information:

Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard.

Classification according to Regulation (EC) No 1272/2008 as amended.

Flam. Gas 1A, H220
Press. Gas Liq. Gas, H280

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 22/41

Other information: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Ensure adequate air ventilation. Ensure all national/local regulations are observed. Ensure equipment is adequately earthed. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

Last revised date: 01.04.2024

Disclaimer: This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended
Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 23/41

Annex to the extended Safety Data Sheet (eSDS)

Content

Exposure Scenario 1.

Exposure scenario worker

1. Industrial:, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Aerosol propellant.

List of use descriptors	
Sector(s) of use	SU0: Other SU24: Scientific research and development
Product categories [PC]:	PC0: Other PC21: Laboratory chemicals

Name of contributing environmental scenario and corresponding ERC	Industrial use: ERC2: Formulation into mixture ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor)

Contributing Scenarios	Industrial use: PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment

	conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC11: Non-industrial spraying PROC15: Use as laboratory reagent

2.1. Contributing exposure scenario controlling environmental exposure for: Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Aerosol propellant.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.

Physical form of the product	See section 9 of the SDS.

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,08 mPa.s (64,2 °F/17,9 °C)

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 25/41

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Handle substance within a closed system.
Air	Air - minimum efficiency of 98 %
Soil	not relevant
Water	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Aerosol propellant.

Process Categories:	PROC1: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions PROC8b: Transfer of substance or mixture (charging and discharging) at dedicated facilities PROC11: Non-industrial spraying PROC15: Use as laboratory reagent

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 % (unless stated differently).

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended
Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 27/41

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	953,25 kPa
Process temperature:	25 °C
Remarks	not relevant

Amounts used

Not relevant.

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Covers daily exposures up to 8 hours		5 days per week	PROC1, PROC8b, PROC11, PROC15

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3				Chemical production or refinery in closed process without likelihood of

air changes per hour).				exposure or processes with equivalent containment conditions
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at dedicated facilities
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Non-industrial spraying
Local exhaust ventilation				Non-industrial spraying
Provide a good standard of controlled ventilation (10 to 15 air changes per hour).				Use as laboratory reagent
Local exhaust ventilation				Use as laboratory reagent

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS. Ensure operatives are trained to minimise exposures. Ensure supervision is in place to check that the RMMs are

				in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:
Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Aerosol propellant.:

none

Health:
Industrial use, Formulation of mixtures with gas in pressure receptacles, Transfilling gas or liquid., Using gas alone or in mixtures for the calibration of analysis equipment., Aerosol propellant.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra

Exposure Scenario 2.

Exposure scenario worker
SDS_SE - 000010021747

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended
Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 30/41

1. Professional:, Use in fuel, Refilling of refrigeration equipment

List of use descriptors	
Sector(s) of use	SU14: Manufacture of basic metals, including alloys
Product categories [PC]:	PC13: Fuels PC16: Heat transfer fluids

Name of contributing environmental scenario and corresponding ERC	Professional use: ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor) ERC9a: Widespread use of functional fluid (indoor) ERC9b: Widespread use of functional fluid (outdoor)

Contributing Scenarios	Professional use: PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC16: Use of fuels

2.1. Contributing exposure scenario controlling environmental exposure for: Professional use, Use in fuel, Refilling of refrigeration equipment

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.

Physical form of the product	See section 9 of the SDS.

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended
Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 31/41

Viscosity:	
Kinematic viscosity:	No data available.
Dynamic viscosity:	0,08 mPa.s (64,2 °F/17,9 °C)

Amounts used

Annual amount per site	The actual tonnage handled per site is not considered to influence the immissions as such for this scenario as there is practically no release

Frequency and duration of use

Batch process:	260 Emission days
Continuous process:	260 Emission days

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Handle substance within a closed system.
Air	Air - minimum efficiency of 98 %
Soil	not relevant
Water	not relevant
Remarks:	not relevant

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 32/41

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		External recovery and recycling of waste should comply with applicable local and/or national regulations.

Additional good practice advice beyond the REACH CSA

Ensure operatives are trained to minimise releases

2.2. Contributing exposure scenario controlling worker exposure for: Professional use, Use in fuel, Refilling of refrigeration equipment

Process Categories:	PROC8a: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities PROC16: Use of fuels

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 % (unless stated differently).

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	953,25 kPa
Process temperature:	25 °C
Remarks	not relevant

Amounts used

Not relevant.

Frequency and duration of use

	Use duration:	Frequency of use:	Remarks
Covers daily exposures up to 8 hours		5 days per week	PROC8a, PROC16

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting workers exposure

Other relevant operational conditions:	. See section 8 of the SDS.

Risk management measures (RMM)

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 34/41

Technical conditions and measures at process level (source) to prevent release

See chapter 7 of the safety data sheet

Technical conditions and measures to control dispersion from source towards the worker

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
Local exhaust ventilation				Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
Provide a basic standard of general ventilation (1 to 3 air changes per hour).				Use of fuels
Local exhaust ventilation				Use of fuels

Organisational measures to prevent/limit releases, dispersion and exposure

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS. Ensure operatives are trained to minimise exposures. Ensure supervision is in place to check that the RMMs are in place and are being used

				correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

See section 7 of the SDS. Handle product within a closed system. Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

3. Exposure estimation

Environment:
Professional use, Use in fuel, Refilling of refrigeration equipment:

none

Health:
Professional use, Use in fuel, Refilling of refrigeration equipment:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Check that RMMs and OCs are as described above or of equivalent efficiency Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see http://www.ecetoc.org/tra

Exposure Scenario 3.

Exposure scenario consumer

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 36/41

1. Consumer, Use in fuel, Aerosol propellant.:

List of use descriptors	
Sector(s) of use	SU0: Other SU14: Manufacture of basic metals, including alloys
Product categories [PC]:	PC0: Other PC13: Fuels

Name of contributing environmental scenario and corresponding ERC	Consumer use: ERC8a: Widespread use of non-reactive processing aid (no inclusion into or onto article, indoor) ERC8b: Widespread use of reactive processing aid (no inclusion into or onto article, indoor) ERC8e: Widespread use of reactive processing aid (no inclusion into or onto article, outdoor)

List of names of contributing worker scenarios and corresponding PROCs	Consumer use: PROC11: Non-industrial spraying PROC16: Use of fuels

2.1. Contributing exposure scenario controlling environmental exposure for: Consumer use, Use in fuel, Aerosol propellant.

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.

Physical form of the product	See section 9 of the SDS.

Viscosity	
Kinematic viscosity	No data available.
Dynamic viscosity	0,08 mPa.s (64,2 °F/17,9 °C)

Amounts used

Amount per use	Not relevant.

Frequency and duration of use

Batch process	< 260 Emission days
Continuous process	not relevant

Environment factors not influenced by risk management

Other given operational conditions affecting environmental exposure

Other relevant operational conditions	not relevant

Risk management measures (RMM)

Technical conditions and measures at process level (source) to prevent release

See chapter 8 of the safety data sheet (Environmental exposure controls).

Technical onsite conditions and measures to reduce or limit discharges, air emissions and releases to soil

Technical and organisational measures	Handle substance within a closed system.
Air	Air - minimum efficiency of 98 %
Soil	not relevant
Water	not relevant
Remarks:	not relevant

Organisational measures to prevent/limit release from site:

none

Conditions and measures related to sewage treatment plant

type:	not relevant
Discharge rate:	not relevant
Treatment effectiveness:	not relevant
Sludge treatment technique:	not relevant
Measures to limit air emissions:	not relevant
Remarks	Wastewater emission controls are not applicable as there is no direct release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Fraction of used amount transferred to external waste treatment:

Suitable waste treatment	Treatment effectiveness	Remarks
See section 13 of the SDS		Dispose of container via supplier only.

Conditions and measures related to external recovery of waste

Fraction of used amount transferred to external waste treatment:

Suitable recovery operations:	Treatment effectiveness	Remarks
See section 13 of the SDS		Dispose of cylinder via gas supplier only; cylinder contains a porous material which in some cases contains asbestos.

Additional good practice advice beyond the REACH CSA

Do not release into the environment.

2.2. Contributing exposure scenario controlling consumer exposure for: Consumer use, Use in fuel, Aerosol propellant.

SAFETY DATA SHEET
According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date: Revision Date: Last revised date :	16.01.2013 01.04.2024 11.04.2022	Version: 2.2	SDS No.: 000010021747 39/41

Product Categories:	PC0: Other PC13: Fuels

Product characteristics

Concentration of the substance in a mixture:	Covers percentage substance in the product up to 100 %.

Physical form of the product:	See section 9 of the SDS.
Vapour pressure:	953,25 kPa
Process temperature:	25 °C
Remarks	not relevant
Application:	not relevant

Amounts used

Handling of product in negligible amounts

Frequency and duration of use

	Use duration (h/d):	Frequency of use:	Remarks
Exposure duration	< 8 hrs	< 5days per week	Intermittent release

Human factors not influenced by risk management

This information is not available.

Other given operational conditions affecting consumers exposure

Area of use	Room size:	Temperature:	Ventilation rate	Remarks
Indoor use				Provide adequate general and local exhaust ventilation.

Other relevant operational conditions	not relevant

Risk management measures (RMM)

Conditions and measures related to information and behavioural advice to consumers

inhalation exposure	dermal exposure	eye exposure	oral exposure	Remarks
				See section 7 of the SDS.
				See section 8 of the SDS.

Conditions and measures related to personal protection, hygiene and health evaluation

See chapter 8 of the safety data sheet (Personal protection equipment)

Additional good practice advice beyond the REACH CSA

Keep away from children.

3. Exposure estimation

Environment:
Consumer use, Use in fuel, Aerosol propellant.:

none

Health:
Consumer use, Use in fuel, Aerosol propellant.:

none

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

Observe consumer instruction/communication on safe use.

SAFETY DATA SHEET

According to Regulation (EC) No. 1907/2006 (REACH) Article 31, Annex II as amended

Propane, pure substance

Issue Date:	16.01.2013	Version: 2.2	SDS No.: 000010021747
Revision Date:	01.04.2024		41/41
Last revised date :	11.04.2022		